

VEHICLE HOIST PRE-USE INSPECTION

Inspection must follow Manufacturer Specifications & WorkSafeBC OHSR 12.80–12.85

Operator:			Hoist ID/Unit No.:				
Department:			Date:				
Location:			This checklist supports the following SWP sections: Pre-Use Requirements, Operational Rules, Housekeeping, and Potential Hazards as outlined in RSS 18.28.XX				
Check boxes accordingly: OK = No Issues NO = needs attention / repair N/A = not applicable							
HOIST CONDITION	Status OK NO N/A			WORKSITE CONDITIONS	Status OK NO N/A		
General condition (no cracks, corrosion, missing parts)	☐	☐	☐	Floor surface is level, solid, unobstructed	☐	☐	☐
Safety decals, load rating plate legible	☐	☐	☐	Area free of debris, tools, spills	☐	☐	☐
Hoist structure free of oil, grease, debris	☐	☐	☐	Adequate lighting around hoist	☐	☐	☐
Lift arms, pads, and adapters undamaged	☐	☐	☐	Adequate clearance overhead	☐	☐	☐
Arm restraints present and functional	☐	☐	☐	Pedestrian/bystander hazards controlled	☐	☐	☐
Mechanical locks / latch teeth undamaged	☐	☐	☐	Ventilation adequate for shop conditions	☐	☐	☐
Cables/chains/pulleys tensioned and intact	☐	☐	☐	PPE worn as required (eyewear, gloves, boots, hearing protection)	☐	☐	☐
Hydraulic cylinders/hoses – no leaks	☐	☐	☐	Other:	☐	☐	☐
Anchor Bolts secure	☐	☐	☐				
Controls operate smoothly	☐	☐	☐				
Safety Locks engage properly	☐	☐	☐				
Emergency Stop functions	☐	☐	☐				

Comments / Concerns:	Operator Signature
Tag or Locked Out Procedure <i>If any item is marked NO, the hoist must be:</i> • Removed from service immediately • Tagged "OUT OF SERVICE" • Reported to Supervisor/Instructor • Not returned to service until repaired and verified safe	
Date and Time :	
Reason for Tag Out (Defects Identified):	